

Technical data sheet

SECCO protective mat



Laminate of non-woven fabric with polyethylene film

PRODUCT DESCRIPTION

Laminate of non-woven fabric with polyethylene film providing high absorption of liquid building materials and tightness in the protected substrate. Also protects against mechanical damage. Has the ability to suppress sounds and vibrations.

ADVANTAGES

- ✓ High absorbency
- ✓ waterproof
- ✓ slip resistance

PRODUCT PARAMETERS

Material:	non-woven fabric, polyethylene film
Colour:	grey
Weight (g/m ²)	190 ± 10%
Length (m):	10.45
Width (mm):	0.965

PACKAGING:

Roll width (m)	Roll length (m)	Quantity per palett (m ²)
0,965	10,45	770

STORAGE

Rolls should be stored in dry rooms, in undamaged original packaging.

APPLICATION For protecting the substrate against such materials as adhesives, paints, solvents used during construction and painting works, as well as mechanical damage, as an underlay for carpets, panels, wooden floors, etc. For increased work safety during renovations and other construction works; protects against unexpected slipping, sliding the ladder, etc.

ASSEMBLY INSTRUCTIONS

The product should be spread on the surface that may be exposed to damage and dirt due to renovation and construction works, foil side to the ground. It is additionally recommended to fix the product bands to one another to provide full protection (preventing product movement).